AD NUMBER AD341098 CLASSIFICATION CHANGES TO: UNCLASSIFIED FROM: CONFIDENTIAL LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;

Administrative/Operational Use; SEP 1959. Other requests shall be referred to Army Electronic Proving Ground, ATTN: SIGPG-OTW, Fort Huachuca, AZ 85613-7063.

AUTHORITY

AEPG ltr dtd 10 Jan 1980; AEPG ltr dtd 10 Jan 1980

AD 341.098

CLASSIFICATION CHANGED
TO: UNCLASSIFIED
FROM CONFIDENTIAL
AUTHORITY:
USAEPG 1+c, 10 Jan 80



UNCLASSIFIED

DISCLAIMER NOTICE

THIS DOCUMENT IS THE BEST
QUALITY AVAILABLE.

COPY FURNISHED CONTAINED
A SIGNIFICANT NUMBER OF
PAGES WHICH DO NOT
REPRODUCE LEGIBLY.

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

NOTICE:

THIS DOCUMENT CONTAINS INFORMATION

AFFECTING THE NATIONAL DEFENSE OF

THE UNITED STATES WITHIN THE MEAN
ING OF THE ESPIONAGE LAWS, TITLE 18,


U.S.C., SECTIONS 793 and 794. THE

TRANSMISSION OR THE REVELATION OF

ITS CONTENTS IN ANY MANNER TO AN

UNAUTHORIZED PERSON IS PROHIBITED

BY LAW.



HEADQUARTERS U. S. ARMY ELECTRONIC PROVING GROUND Fort Huachuca, Arizona

USAEPG-SIG 930-117, Plan of Test, Task 24-58-0262, "Operational Evaluation of the AN/AAD-2 Drone Infrared Detector (U)" has been prepared by the Combat Surveillance and Avionics Department and is published for the information of all concerned. Distribution of this publication has been approved under the provisions of paragraph 7h, AR 310-1, by the Adjutant General acting for the Secretary of the Army, 21 November 1958. Suggestions or comments relative to this report are invited and should be addressed to the Commanding General, U. S. Army Electronic Proving Ground, Fort Huachuca, Arizona, ATTN: SIGPG-OTW.

FOR THE COMMANDER:

OFFICIAL
MARSHALL CONNELL
Captain, AGC
Asst Adjutant General

CHARLES H. BURCH Colonel GS Chief of Staff

DISTRIBUTION: (Special)

C IV

PLAN OF TEST

OPERATIONAL EVALUATION OF THE AN/AAD-2 DRONE INFRARED DETECTOR (U)

Task 24-58-0262

AUTHORITY

(U) The authority for this test is documented under approved USAEPG Task 24-58-0262, "Drone Infrared Detector (U)," of the USAEPG Technical Program.

OBJECTIVE

Est Plans 2 (U) The objective is to determine the day and night surveillance capabilities of the AN/AAD-2 Drone Infrared Detector when installed and operated in the SD-1 and SD-2 surveillance drones and Army L-20 aircraft.

> September 1959 U. S. Army Electronic Proving Ground Combat Surveillance and Avionics Department Fort Huachuca, Arizona



TABLE OF CONTENTS

		Page
Authority an	nd Objective	1
I. Backs	ground	5
II. Desci	ription of Materiel	7
III. Speci	fic Tests	12
IV. Gener	ral	13
Annex A - D	Petails of Test	15
a. R b. Si 2. Test 3. Test 4. Test 5. Test 6. Test	equirements Available within Department upport Requirements (outside CS and AD) Nr 1 - Target Detection Capabilities Nr 2 - Telemetering Range Nr 3 - Remote Control Nr 4 - Resolution Nr 5 - Line Voltage Variation	15 15 16 16 17 17
Annex B - D	ata Sheet, AN/AAD-2 Drone Infrared Detector 2	21
Annex C - Da	ata Sheet, AN/AAD-2 Ground Station	23
Annex D - Da	ata Sheet, AN/AAD-2 Airborne Equipment 2	25
	aintenance Data Sheet, AN/AAD-2 Drone Infrared	27
Distribution	List	29

TABLE OF CONTENTS (Continued)

LIST OF ILLUSTRATIONS

Figure		Page
1.	Airborne equipment	. 8
۷.	Ground equipment	10
3.	Artist's conception of the equipment in a tactical	
	situation	11
4.	Resolution layout	18

U. S. ARMY ELECTRONIC PROVING GROUND Fort Huachuca, Arizona

PLAN OF TEST - TASK 24-58-0262

OPERATIONAL EVALUATION OF THE AN/AAD-2 DRONE

INFRARED DETECTOR (U)

I. (C) BACKGROUND

1. When it became apparent that the construction of a drone infrared reconnaissance device was within the state-of-the-art, Combat Surveillance and Avionics Department, U. S. Army Electronic Proving Ground, Fort Huachuca, Arizona, prepared technical requirement TR-BASD-2-56 defining the design specifications for such a device. A contract was awarded to Servo Corporation of America for the construction of this equipment.

The AN/UAS-1 Drone Infrared Detector was then developed, laboratory and field tested, and the results evaluated. From these results it was determined that an airborne drone detector required increased ruggedness and reliability, higher resolution, inflight recording, direct liquid nitrogen cooling, and an increased field of view.

On 15 January 1958, USAEPG set forth TR-CSD-23-58 to meet the above requirements for a drone infrared detector that would be operational in the SD-1, SD-2, and SD-3 surveillance drones and also in a manned Army L-20 aircraft. (The SD-3 Drone was later deleted from USAEPG's program.)

A contract (DA-36-039-SC-80074) was awarded Haller, Raymond, and Brown, Inc., of State College, Pennsylvania, for the fabrication of three such airborne infrared drone detectors. One detector (AN/AAD-2) has been received for test and evaluation. These units are based on the principle of a line scanning device that collects the infrared

5

radiation from an object on the earth and images this radiation on an infrared detector. The output of this detector is amplified and presented for viewing and film recording. The trade name "Reconofax" has been given to all such equipments developed by Haller, Raymond, and Brown, Inc.

5

II. (C) DESCRIPTION OF MATERIEL

2. The drone detection equipment for the SD-1 and SD-2 Drones and Army L-20 aircraft is an air-to-ground device using passive infrared detection principles. The airborne equipment, which weighs 44 pounds, consists of a combined optical scanner, glow tube recording unit and a radio link for transmitting the scanner video data to a ground station. (See figure 1.)

The scanner-recording unit combines two separate functions: scanning the terrain beneath the aircraft and recording the output of the glow tube on 70mm recording film.

A lead selenide detector cell, sensitive in the 1-7 micron range, is equipped with an optical filter to filter out radiation below one micron. The lead selenide detector cell is cooled by direct liquid nitrogen (-196°C).

To permit day operation and for use in the 1 - 3.5 micron region of the spectrum, an uncooled lead sulfide detector is furnished.

Roll stabilization of the recording film transport is achieved by the use of a Kearfott Vertical Gyro.

The ground-based presentation and recording unit of the AN/UAS-1 Infrared Detecting Set will be used with the AN/AAD-2 Drone Detector. This ground-based unit was fabricated by the Servo Corporation of America in accordance with contract DA-36-039-SC-67869. Necessary modifications to the ground station will be made by Haller, Raymond, and Brown, Inc., in accordance with the present contract DA-36-039-SC-80074.

The ground-based station converts the received signals into a video presentation that can be recorded on 35mm film, magnetic tape, and/or viewed directly on a cathode-ray presentation screen. This unit uses a standard non-directional ground plane antenna and

7





Figure 1. Airborne equipment.

8

UNCLASSIFIED

commercial FM telemetering receiver. The ground-based unit consists of the following four major components (figure 2):

- a. Receiving Unit. This FM receiving unit completes the radio link between the airborne and ground equipments.
- b. Signal Processing Unit. The signal processing unit converts telemetered composite signals, received by the receiving unit, to a form suitable for use on the visual display and film recording units.
- c. Visual Presentation Unit. This unit provides complete presentation of signals, on a long persistence cathode-ray tube, originating from ground targets.
- d. Film Recording Unit. The Oscillo-Record Camera records the data on 35mm film. Figure 3 represents an artist's conception of the equipment in a tactical situation.



10

UNCLASSIFIED

Figure 2. Ground equipment.




Figure 3. Artist's conception of the equipment in a tactical situation.

11

III. (U) SPECIFIC TESTS

- 3. Details of test are covered in ANNEX A.
- 4. TEST NR 1 TARGET DETECTION CAPABILITIES. To determine what types of selected military and civilian targets can be detected at altitudes ranging from 500 to 3,000 feet.
- 5. TEST NR 2 TELEMETERING RANGE. To determine the maximum useful range of the telemetering link.
- 6. TEST NR 3 REMOTE CONTROL. To determine the effectiveness of remote operation of the scanning unit from the pilots compartment of an Army L-20 aircraft. This test will also determine the effectiveness of remote operation of the scanning unit from a ground-based radar control station when the unit is installed in the SD-1 and SD-2 Drones.
- 7. TEST NR 4 RESOLUTION. To determine the maximum angular resolution of the equipment utilizing both the 3 and 6 mil detector cells.
- 8. TEST NR 5 LINE VOLTAGE VARIATION. To determine the effects upon the scanning unit due to variations in the voltage.
- 9. TEST NR 6 REPRODUCIBILITY OF TAPE RECORDED DATA. To determine to what degree mapping data is reproducible after being recorded on magnetic tape.

IV. (U) GENERAL

10. RESPONSIBILITY.

- a. Optics Division, Combat Surveillance and Avionics Department, is the responsible organization for conducting the test.
 - b. Mr. Richard W. Fulton is the Project Officer.

11. REPORTS.

- a. Partial reports will be submitted as deemed necessary.
- b. A final report will be submitted upon completion of tests.

Colonel

SigC

Acting Chief

ANNEX A - DETAILS

OF TEST

ANNEX B - DATA SHEET

AN/AAD-2 DRONE

INFRARED DETECTOR

ANNEX C - DATA SHEET

AN/AAD-2 GROUND

STATION

ANNEX D - DATA SHEET


AN/AAD-2 AIRBORNE

EQUIPMENT

ANNEX E - MAINTENANCE DATA SHEET

AN/AAD-2 DRONE

INFRARED DETECTOR



ANNEX A - DETAILS OF TEST

- 1. (U) GENERAL.
 - a. Requirements Available within Department
 - (1) Equipment Requirements
 - (a) Three drone infrared scanners
 - (b) Ground-based unit (AN/UAS-1)
 - (c) ARC-12 Type Radio Set
 - (d) Ten kerosene flare pots
 - (e) Two trucks, 3/4 ton, 4 x 4 (targets)
 - (f) Two trucks, 2-1/2 ton, 6 x 6 (targets)
 - (g) Two trucks, 1/4 ton, 4 x 4 (targets)
 - (h) Liquid nitrogen
 - (i) Power Unit, PE-95
 - (j) Drones (SD-1 and SD-2)
 - (2) Personnel Requirements
 - (a) One airborne operator
 - (b) Two ground station operators
 - (c) Photo laboratory technician
 - (d) Six truck drivers
 - (e) Drone operator crew
 - (f) PE-95 operator
 - b. Support Requirements (outside CS and AD)
 - (1) Equipment Requirements

Army aircraft, L-20

A - page 1

(2) Personnel Requirements

Army aviator

2. (C) TEST NR 1 - TARGET DETECTION CAPABILITIES.

- a. Purpose. To determine what types of selected military and civilian targets can be detected at altitudes ranging from 500 to 3,000 feet above terrain.
- b. Method. When placed in an Army L-20 aircraft, the scanning unit will be flown over selected local targets at altitudes of 500, 1,000, 1,500, 2,000, 2,500, and 3,000 feet above terrain. Tests will be performed both day and night under prevailing permissible flight conditions at Fort Huachuca, and different types of available detector cells will be used.

After the manned aircraft tests, the scanner will first be mounted in an SD-1 Drone and tested at the Proving Ground. Then it will be placed in an SD-2 Drone and tested at the test range in Yuma, Arizona. The Drones will be flown at the previous mentioned altitudes over various available military type targets.

c. Data to be Recorded. As specified on Data Sheet, annex B.

3. (C) TEST NR 2 - TELEMETERING RANGE.

- a. Purpose. To determine the maximum useful range of the telemetering link.
- b. Method. The ground station placement will provide a clear line-of-sight for at least 50 miles to a point 1,000 feet above terrain. Flights will be made in an Army L-20 aircraft, SD-1 and SD-2 Surveillance Drones. The aircraft will fly at a 1,000 foot altitude until a useful telemetered signal is no longer obtained at the ground station. (A useful signal is defined as that giving a recognizable presentation at the ground station of a designated target.) This test will be performed four times; drone testing will not be attempted until all tests with manned aircraft have been performed.
- c. Data to be Recorded. Position of ground tracking station and position of aircraft when useful transmission ceases. Film will be adequately marked.

A - page 2

4. (C) TEST NR 3 - REMOTE CONTROL.

- a. Purpose. To determine the effectiveness of remote operation of the scanning unit from the pilot's compartment of an Army L-20 aircraft. This test will also determine the effectiveness of remote operation of the scanning unit from a ground-based radar control station when the unit is installed in the SD-1 and SD-2 Drones.
- b. Method. The equipment will be remotely operated from the front seat of an Army L-20 aircraft. After all phases of testing have been completed in the manned L-20 aircraft remote operation of the scanner from the ground-based unit will be performed.
- c. Data to be Recorded. Readings from the remote-control indicator box and any other pertinent information.

5. (C) TEST NR 4 - RESOLUTION.

- a. Purpose. To determine the angular resolution of the equipment utilizing both the 3 and 6 mil detector cells.
- b. Method. The equipment will be flown both day and night in an Army L-20 aircraft over preselected targets of known dimensions and spacing at a series of altitudes in 500 foot increments. (See figure 4.)
- c. Data to be Recorded. All information specified on the ground station and airborne Data Sheets. (Annexes C and D.)

6. (C) TEST NR 5 - LINE VOLTAGE VARIATION.

- a. Purpose. To determine the effects upon the scanning unit due to variations in the line voltage.
- b. Method. In the laboratory the drone scanner will be connected to a variable voltage power supply and the voltage varied from 22 to 30 volts in increments of one volt.
 - c. Data to be Recorded. Effects upon scanner operation.

A - page 3




Figure 4. Resolution layout.

18

UNCLASSIFIED

7. (C) TEST NR 6 - REPRODUCIBILITY OF TAPE RECORDED DATA.

- a. Purpose. To determine to what degree mapping data is reproducible after being recorded on magnetic tape.
- b. Method. The tape recorder will be used in Army L-20 aircraft and SD-1 and SD-2 Drones on at least 10 flights to gather infrared information.
 - c. Data to be Recorded. Adequacy of data for reproduction.
- 8. (C) During Tests 1 through 6 data will be recorded to determine the following:
 - a. Time needed to train personnel to operate equipment.
 - b. Equipment preparation time and difficulties encountered.
- c. Settings, alignment, and procedures of operation to obtain optimum performance.
- d. Comparison of ground record 35mm and air record 70mm recording film.
 - e. Effects of vehicle handling and aircraft vibration.
- f. Maintenance requirements with respect to breakdown frequency, difficulty of repair, spare parts requirements, and test equipment requirements. (See Data Sheet, Annex E.)
 - g. Factors affecting reliability and ease of operation.
- h. If the "Operational and Maintenance Handbook" is adequate for clarity and completeness of written matter, photographs, and schematics.

. • • •

ANNEX B - DATA SHEET

AN/AAD-2 DRONE INFRARED DETECTOR

FLIGHT	DETECTOR CELL
DATE	OPERATORS:
TIME: Flight	Ground
Equipment Operated	
AREA	AUTOMATIC GAIN CONTROL (AGC) LEVEL
PILOT	(AGC) LEVEL
FILM FOOTAGE:	FILM TYPE:
(Air) Start	Air
Finish	Ground
(Ground) Start	
Finish	
WEATHER:	
Air Temperature	
Ground Temperature	
Visibility	
Relative Humidity	
Precipitation	



ANNEX C - DATA SHEET
AN/AAD-2 GROUND STATION


REMARKS				•			
ELEVATION							
DIRECTION							
N/H							
TARGET							
RUN NR							

*** ~

ANNEX D - DATA SHEET

AN/AAD-2 AIRBORNE EQUIPMENT

REMARKS							
ELEVATION							
DIRECTION							
ИЛН							
TARGET							
RUN NR							



ANNEX E

MAINTENANCE DATA SHEET

AN/AAD-2 DRONE INFRARED DETECTOR

INDICATION OF MALFUNCTION:

ANALYSIS OF MALFUNCTION AND CAUSE:	SIGNED
	DATE
CORRECTION OR REPAIR:	
REMARKS:	SIGNED
NEWACKS:	SIGNED
	DATE

DISTRIBUTION LIST USAEPG-SIG 930-117 9-59

Reports are firmished for information and retention. When no longer required, reports should be discarded or, if classified, destroyed in accordance with AR 380-5.

ADVANCE DISTRIBUTION

	Nr of Cya	N	r of Cye
Chief Signal Officer Department of the Army Washington 25, D. C. ATTN: SIGRD	5	Commanding Officer U. S. Signal Communication Engineering Agency Waahington 25, D. C.	1
Commanding Officer U. S. Army Signal Research and Development Laboratorica Fort Monmouth, N. J. ATTN: SIGFM/EL-ADT	1	Commanding Officer 9550 TSU, Project Michigan Willow Run Research Center Ypsilanti, Michigan	ı
Commanding Officer U. S. Army Signal Research and Development Laboratoriea Fort Monmouth, N. J. ATTN: SIGFM/EL-ENC	6	Electronic Defense Group Engineering Research Institute University of Michigan Ann Arbor, Michigan	1
Commanding Officer U, S. Army Signal Research and Development Laboratories Fort Monmouth, N. J. ATTN: SIGFM/EL-RE	1	Commanding General U. S. Army Signal Air Defense Fort George Meade, Maryland ATTN: SIGAD-7-A	1
Commanding Officer U. S. Army Signal Research and Development Laboratories Fort Monmouth, N. J. ATTN: SIGFM/EL-DP	2	Commanding General U. S. Army Combat Surveillance 1124 N. Highland St Arlington 1, Va	1
Commanding Officer U. S. Army Signal Equipment Support Agency Fort Monmouth, N. J.	ı	Commanding General U. S., Army Signal Supply Agency Philadelphia, Pa ATTN: Deputy for Mobilization	1
Commanding Officer U. S. Army Signal Publicationa Agency Fort Monmouth, N. J. (Uncl only)	1	Commanding General U. S. Army Signal Training Center Fort Gordan, Georgia	1
President U. S. Army Signal Board Fort Monmouth, N. J.	ı	Commandani U. S. Army Signal School Fort Monmouth, N. J.	3
Commanding General U. SArmy Continental Army Command Ft Monroe, Va ATTN: ATSIG a. Reports b. Teat Plana	2	Commandant U. S. Army Signal School ATTN: Signal Corps Doctrine Div Pt Monmouth, N. J.	5
		Internal USAEPG	45

REGULAR DISTRIBUTION

USAEPG-SIG 930-117

Nr of Cys

Nr of Cys

Commanding Officer U. S. Army Signal Intelligence Agency Arlington Hall Station Arlington 12, Virginia	1	Commanding General U. S. Army Combat Development Experimentation Center Fort Ord, California
Chief of Research and Development Department of the Army Washington 25, D. C.	2	Director Office Special Weapons Development Fort Bliss, Texas
President U. S. Army Artillery Board Fort Sill, Oklahoma	1	President U. S. Army Intelligence Board Fort Holabird, Maryland
President U. S. Army Infantry Board Fort Benning, Georgia Commandant	1	a. Unclassified Reports: Canadian Liaison Officer, Dir, CDEV Fort Huachuca, Arizona
Command and General Staff College Fort Leavenworth, Kansas ATTN: ALLIS (AS)	2	b. Classified Reports: ACofS Intel (Can LnO) Fort Huachuca, Arizona
Director Marine Corps Development Center Marine Corps Schools Quantico, Virginia	2	a. Unclassified Reports: British Liaison Officer, Dir, CDEV Fort Huachuoa, Arisona
Commanding Officer U. S. Army Signal Electronic Research Unit Post Office Box 205 123 North Whisman Rd		b. Classified Reports: ACofS Intel (Brit LmO) Fort Huachuca, Arizona
Mountain View, California Commanding General	1	
U. S. Continental Army Command Fort Monroe, Virginia ATTN: ATDEV-5 (1 copy only for Plan of Test)	4	

UNCLASSI fied